


Single Door Underbench Storage Refrigerators and Freezers

Features:

- Lockable door with handles
- Digital controller and digital temperature display
- Adjustable feet
- Frequency/voltage: 50Hz/220-240 V
- Plastic coated steel shelves
- Refrigerant: R134a
- Ambient temperatures +16°C to +32°C



MC200H



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 140 L

Exterior dimensions in mm: 600w x 615d x 845h

Number of adjustable shelves: 3

Cooling system: static, fan assisted

Defrost system: manual

Temperature set range: 0°C to +10°C


Gross/net weight: 55/45 kg

Door material: stainless steel

Energy consumption in 24h: 2 kWh

\$1,700.00+GST

MC200G



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 140 L

Exterior dimensions in mm: 600w x 615d x 845h

Number of adjustable shelves: 3

Cooling system: static, fan assisted

Defrost system: manual

Temperature set range: 0°C to +10°C

Gross/net weight: 55/45 kg

Door material: glass

Energy consumption in 24h: 2 kWh

\$1,800.00+GST


MF200H



Fixed top evaporator shelf with railing guard



Sliding drawers for middle and bottom shelf



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 140 L

Exterior dimensions in mm: 600w x 615d x 845h

Fixed shelves: 1 + 2 sliding drawers

Cooling system: static

Defrost system: manual

Temperature set range: -10°C to -22°C

Gross/net weight: 55/45 kg

Door material: stainless steel

Energy consumption in 24h: 3 kWh

\$1,800.00+GST